

HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com



Facebook

IS045001:2018



YouTube

IS014001:2015



WeChat







Forklift" App







 ${\it HANGCHA\ GROUP\ CO., LTD.}\ reserves\ the\ right\ to\ make\ any\ changes\ without\ notice\ concerning$ colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

IS09001:2015



X Series Diesel Counterbalanced Forklift Trucks

with capacities of 12,000kg





DIESEL COUNTERBALANCED FORKLIFT TRUCKS

The X series is the new series of internal combustion counterbalance forklift truck developed by Hangcha independently, adopting the advanced technologies based on the original products. Through the comprehensive upgrading of appearance molding, energy conservation, environmental protection, comfort, security and reliability, it will become the forklift truck which can meet your overall demands.

Strong appearance and visual impact

The appearance of full vehicle is developed under the cooperation with professional industrial design company by adopting the appearance design methods of brand-new concept. The streamlined surface modeling design brings smooth lines, elegant appearance, vigorous and steady surface as well as the outstanding inherence, possessing the powerful visual impact.

The appearance of full vehicle is exquisite and concise. which adopting the newly designed parts with opening mould at large area, the appearance of full vehicle will be more humanized.

Innovation design



The new designed mast increase forward visibility 15%

controlled engine provide lower failure rate



Legroom ↑15%



Fuel consumption ↓10% (Common rail engine)



Exhaust emission ↓ 35%



(Common rail engine)



Aluminous plate-fin radiator provides stronger structure



Grade-speed ability † 15%



Better cold starting performance (Common rail engine)



Water temp ↓ 10 °C, oil temp ↓ 10%





(Common rail engine)



Fully improved reliability and security









The radiator adopts aluminous plate-fin radiator with better performance and higher structural strength. Impendent oil radiator, optimized oil and water heat dissipation channel and double ventilation holes on counterweight can greatly improve cooling efficiency and reliability of overloaded operation and ensure reliable operation of the engine.

Overhead guard adopts special-shaped steel tube, which can reinforce the strength and improve sealing of the cab.

Roller bearing on the steering axle king pin adopts large size tapered roller bearing (TRB), larger steering cylinder and bumper block assemblies on the top, which can prolong the service life of bearing and highly improve the reliability of steering axle.

Along with adopting a low height for the step, it has also been made wider, facilitating frequency entry and exit.

Energy conservation and environmental protection



The whole truck adopts LED lights as shiner and new-type panoramic retroreflector to ensure energy conservation and power saving as well as greatly improve the performance and service life of luminaires at the same time.

The full vehicles all adopt the environmental protection material to reduce environmental hazards.



Easy maintenance



Newly-developed LCD instrument has more comprehensive functions and more stable performance and entirely displays the full vehicle running state, trouble diagnosis and other important information, which can make the operator more intuitively and conveniently have a better knowledge of vehicle state and make the maintenance


conveniently.



The enlarged opening angle of hood and increase of left and right hood side plates can mainte provide you with convenient convenient and rapid maintenance mode.



Integral locking pin structure
on the baseboard can be
opened without tool, which is
convenient for daily repair and
maintenance.



Comfort

Reduce the caster angle of instrument stand and adopt the integral hood to greatly increase the space underfoot;

The orthodrome of overhead guard fore leg will expand the driving space;






Optimized air intake and exhaust system of full vehicle, high-capacity exhaust silencer will reduce the noise of full vehicle and reduce the vibration.



The design of steering wheel of small diameter and electro-hydraulic reversing as well as the car-type double-handle combination switch will greatly improve the driving comfort.



Adopt the new-type of box iron. Increase the inside width of inner mast and the spacing between lifting cylinders. The lowering of instruments in the driving cab will greatly increase the forward visibility; The rear visibility will also be greatly improved through the optimization design of counterweight.

Bosch High Pressure CommonRail Technolgy

Engine equipped with Bosch high pressure common rail electronic control, adopting high pressure multiple injection technology, strong power output, lower smoke emission, better cold start performance, and energy saving by 10%.



Standard Specification

- / Caliper disc brake
- / Working light
- / Hydraulic oil filter
- / Electric Flameout
- / Seat with belt
- / Skidproof pedal
- / Air filter
- / Hydraulic oil dipstick
- / Traction device
- / Mast speed limiting valve
- / Full hydraulic power steering
- / Wide view duplex mast
- / Standard forks
- / Standard overhead guard
- / Rear combination LED light
- / panoramic rearview mirror
- / Adjustable steering column
- / Pre-heating indicator
- / Engine fuel pressure warning
- / Neutral switch
- / Engine hood spring
- / Dipstick
- / Cover of tilt cylinder
- / Horn
- / Fuel gauge
- / LCD display
- / High-positioned intake system
- / High-positioned exhaust system
- / Cable parking brake
- / Tilt cylinder self-locking valve
- / Timer
- / Port type gearbox
- / Charging indicator
- / Water temperature gauge
- / Air filter alarm lamp
- / Reversing buzzer
- / Hand grip
- / Integrated controller
- / Oil-water separator
- / Multiplex hydraulic valve
- / Wider fork carriage
- / Emergency switch
- / Fork positioner

Optional Mast

- / Duplex wide view full free mast
- / Trilex wide view full free mast
- / Special duplex wide view mast
- / Special forks

Options

- / Cabin
- / Intelligentized management system
- / Customer painting
- / Cabin heater
- / LED rear working light
- / Hood lock
- / Solid tyre
- / Middle-positioned exhaust system
- / Sparkle arrester
- / Suspension seat
- / Fuel tank lock
- / Extinguisher
- / Dual air filter
- / Toolbox
- / Warning light

Optional Attachments

- / Paper roll clamp
- / Load stabilizer
- / Side shifting fork positioner
- / Bale clamp
- / Steel pipes Hinge Fork
- / Dumping clamp
- / Crane arm
- / String pole
- / Sideshifter / Rotating forks
- / Fork extensioner
- / Tyre handler
- / Block clamp
- / Bucket

