#### Features

Truck	Standard	Options
Standard battery	•	
Side charging (lithium battery)	•	
Side shift battery	•	
Terminal power (12V)	•	
Large-capacity lithium battery		0
Platformrail		0
Non-standard series fence		0
Charger		0
Solid tire		0
Non-standard color		0
Cab		
Tool box	•	
Document bin	•	
Cupholder	•	
Tilt-adjustable steering wheel	•	
Fully suspended console	•	
Seat	•	
Seat belt	•	
Reflective mirror		0
Large-diameter steering wheel		0
Suspended seat		0
Controls and instruments		
LCD display	•	
Safety		
Emergency power-off switch	•	
Horn	•	
Reverse buzzer	•	
Electromagnetic parking brake	•	
Acoustic and optical alarm		0
Reverse voice buzzer		0
Fire extinguisher		0
Lights		
LED integrated headlights (near and far turning streamer)	•	
LED rear combination tri-color light LCD display	•	
Alarm light		0
Daytime running blue light	•	
LED rear operation light	•	

#### Features(Optional configuration for models with cabs)

Cab	Standard	Options
Fully enclosed cab		0
Semi-enclosed cab		0
Boarding handle		0
Rearview mirror		0
Ceiling light		0
Fan		0
Front single-sheet wiper		0
Front wiper injector		0
Sunshade		0
Front glass defroster		0
Heater		0
Cooling and heating air conditioner		0

Note: The fan is usually selected for the canopy or cab, and is not recommended to be selected separately; the cab and canopy are equipped with standard reflectors; the daytime running blue light is usually selected with the canopy or cab, and is not recommended to be selected separately.

#### HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.




























HANGCHA provides Li-ion battery (LiFePO4) with 6 years or 12000 hours warranty.



# INNOVATIVE SOLUTIONS NEW POWER NOW

- / We use square lithium iron phosphate batteries and modules used in large quantities by commercial vehicles in mature economies.
- / Safe and effective: Charging efficiency as high as 95%.
- / Quick charging.
- / Long-working: 4000 charging cycles, capacity retention greater than 75%.
- / Maintenance-free: Battery does not require manual maintenance.
- / Green and clean: Pollution-free, zero emissions.





## Rapid charging and opportunity charging ensure continuous availability of vehicles

Allow for fast full charging or boost charging.

They are maintenance free and do not require a battery change when used for multi-shift operations.





#### Console:

Integral fully-suspended console, flexible connection with the frame, vibration and noise isolation, good comfort.

#### Front anti-collision bumper:

steel plate type front anti-collision bumper, safer and good energy absorption.

#### Suspended seat:

strong shock absorption, good comfort. (optional)

#### LED headlamp:

the LED integrated headlamps have daytime running lamps, far/near light, front turning streamer and other functions, safe and energy-saving.

#### Fully hydraulic steering:

standard follow-up steering system, boasting low energy consumption, low noise, light control force, safe and reliable steering, etc. advantages.



#### **RELIABILITY AND SAFETY**

- The efficient AC power system has standard electromagnetic brake, automatic parking and complete protection functions, greatly improving reliability and service life.
- The electrical components are arranged at height, and the whole vehicle has a high protection level.
- With the battery placed at the bottom of the vehicle frame, the vehicle has good stability, both safe and reliable.







### REVOLUTIONARY **PERFORMANCE**

High-voltage platform, light weight and low power consumption. Long endurance mileage, optional lithium batteries and large-capacity lead-acid batteries available for the whole series.



Oj	ptional batte	ry list(EVE)	
Capacity(Ah)	8t(80V)	10t(80V)	16t(96V)
230	•	•	1
304	0	0	•

Optional battery list(Tian neng)				
Capacity(Ah)	8t(80V)	10t(80V)		
250	0	1		
275	0	1		
300	0	0		
350	/	1		
385	/	1		
420	/	/		

Note: ● Standard battery capacity; ○ Optional battery capacity;



#### **ADVANCEMENT**

High-power AC asynchronous motor + vector control + high efficiency gearbox with large speed ratio can achieve high driving speed, good acceleration performance, high speed for heavy-duty vehicles, high gradient climbing, and large load capacity, featuring high control precision, fast startup, low energy consumption and noise.



10X50<sub>%</sub> Max. gradeability(laden)





The large-screen anti-glare LCD display adopted can display power, speed, mileage, fault and other information clearly and accurately even in harsh environments.



The whole vehicle is equipped with LED, and the integrated headlamps have daytime running lamps, far/near light, front turning streamer and other functions.



Large ground clearance, small turning radius, good passing ability.

#### **GREAT COMFORT**

- Front and rear axles adopt full elastic suspension system, exhibiting low vibration and good smoothness.
- Fully hydraulic steering, standard follow-up steering system, boasting low energy consumption, low noise, light control force, good hand feeling, safe and reliable steering.





Integral fully-suspended console, double-floating design, vibration and noise isolation, good comfort.



Large open pedals at low position, more legroom, more convenient to get on and off the vehicle.

#### **MAINTAINABILITY**

Removed from a side of the vehicle, the battery provided in the standard configuration can be repaired, replaced and maintained more easily and is applicable to continuous operating conditions.

■ Electric control and electrical components are integrated in the electric control door with latch, which is convenient for debugging and maintenance of the electric control system.

Table of 0-10 charlot in and reflect specification recommendation				
Length Width	3200	4000	5000	6000
1800	Standard	0		0
2050	Standard	Standard	0	0
2600		0		0

Note: • Preferred: Optional Vehicle fence height: 320mm

