



**HANGCHA GROUP CO., LTD.**

**Factory site:** 666 Xiangfu Road,  
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755  
Fax: +86-571-88926789 88132890

sales@hcforklift.com  
www.hcforklift.com



Follow us on  
Facebook



Follow us on  
YouTube



Follow us on  
WeChat



Download "Hangcha  
Forklift" App



ISO45001  
ISO45001:2018



ISO14001  
ISO14001:2015



ISO9001  
ISO9001:2015



HANGCHA trucks conform  
to the European Safety  
Requirements.

2024 VERSION 1/COPYRIGHT 2024/04

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



## A Series Pallet Truck Basic Range

with capacities of 2,000kg

*The World of Hangcha*



## High Performance

- / AC travelling motor applied to provide excellent acceleration, good gradeability, low heat, no carbon brush and maintenance free.
- / The latest CURTIS AC control system provides accurate and stable control to work more efficient.
- / The applied CANBUS structure to offer more reliable and faster command access.
- / Regenerative brake and slope anti-slide function are offered by this truck.

## Comfort

- / The shock absorption design of foldable platform improves comfort greatly to the operator.
- / Simple and beautiful tiller designed to operate all functions easily even by one hand.
- / Displayed turtle speed function applied to move slowly and helps to stack goods in narrow spaces.
- / Optimized designing structure to offer a good visibility and easy entrance of the pallet.
- / The compact body and big rounded design provide an ideal operation in limited space, and the wedge designed chassis greatly increases the passing ability.

## Reliability

- / Five-pivot with low centre of gravity design and high strength steel frame structure chassis provide larger residual load capability and longer working life.
- / Water-proof plugs and connectors applied to provide a reliable protection to electric system.
- / The adopted unique floating suspension system ensures good driving wheels' grip and excellent stability.
- / Top quality hydraulic power unit applied to provide low noise, low vibration, smooth lifting and landing reliable operation.
- / Punch-formed forks to provide more strength and tip guide to provide higher efficient operation.
- / The power plug is fixed on the truck body to avoid damage from battery installment.

## Safety

- / With three braking types: releasing brake, reversing brake and emergency brake, the driving safety has been ensured.
- / The applied slope anti-slip function ensures the safety of the operation.
- / The emergency button on the tiller head can effectively avoid the harm to the driver.
- / The standard equipped electronic lifting limitation and intellectual control limitation to offer double protection to working motor and loads from damaging.



## Standard Specification

- |                            |  |
|----------------------------|--|
| / Horn                     | / Hydraulic power unit                 |
| / Pedal (only CBD20-AEC1S) | / 540mm outside fork width             |
| / AC drive wheel           | / Electronic lifting limitation        |
| / Tandem load wheels       | / Emergency disconnect switch          |
| / 1150mm fork length       | / Multi-function battery indicator     |
| / CURTIS AC controller     | / CAN-bus system multi-function tiller |

## Options

- / Load backrest
- / Guide roller of pallet
- / Handrail
- / 210Ah, 240Ah, battery
- / Different outside fork width (560mm, 600mm, 650mm, 680mm, 700mm)
- / Cold store protection (-30 °C)
- / Different length of forks (1220mm, 1400mm, 1600mm, 2000mm, 2150mm, 2400mm)



**Stand-on**