



**HANGCHA GROUP CO., LTD.**

**Factory site:** 666 Xiangfu Road,  
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755  
Fax: +86-571-88926789 88132890

sales@hcforklift.com  
www.hcforklift.com



Follow us on  
Facebook



Follow us on  
YouTube



Follow us on  
WeChat



Download "Hangcha  
Forklift" App



ISO14001  
ISO14001:2015



ISO9001  
ISO9001:2015



HANGCHA trucks conform  
to the European Safety  
Requirements.

2026 VERSION 1.1 COPYRIGHT 2026/03

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

# X Series Empty Container Handler

with capacities of 9,000kg

**STAGE V**  
CERTIFIED

**REACH**  
THE SKY



*The World of Hangcha*  
SINCE 1956



## X Series Empty Container Handler

A new generation high-quality professional product, which is newly developed on the basis of Hangcha's X series platforms and years of industry experience and extensively adopts advanced technologies, is mainly used in the loading, handling and stacking operations of empty 20ft and 40ft ISO containers.

### Reliable

- / The gearbox(DANA), drive axle(KESSLER), engine and key hydraulic parts are all have stable and reliable quality.
- / The accumulated years of industry experience, digital product design, finite element analysis, kinematic and dynamic simulation calculation, field verification, and fatigue, overload, strain tests ensure the reliable structure of the truck.
- / The mast is made of high-strength steel and has an ultra-wide structure designed. The installation point of the inclined oil cylinder is arranged at a high position to improve the rigidity and stability of the truck.
- / The truck's heat dissipation management system automatically adjusts the heat dissipation intensity, so that each system can quickly enter the efficient operating state. The large heat dissipation capacity design ensures the requirements for the heat dissipation in high temperature environments to be met.
- / With waterproof and dust-proof design, the electrical system has higher reliability.
- / The novel spreader has a higher reliability, a longer service life, a lower failure rate and a lower maintenance cost.





## Comfortable

- / The instruments with high-definition color screens display the truck status in real time and the fault alarm enable easier maintenance.
- / The new generation electronically-controlled gearbox enables flexible, smooth and comfortable gear shifting.




## Efficient

- / The throttle following control provided for controlling the engine speed, the single-hand joystick and the electric proportional control enable flexible, accurate and efficient control.
- / Higher lifting speed and faster dynamic response enable the operation efficiency to be effectively improved.
- / Easy maintenance design a wide-opened hood, a large-space electric control box, a larger cab space, multiple hydraulic inspection points, easy access to the oil and water during inspection, and built-in diagnostic and query functions of the smart instruments.



## Safe


- / The spreader twist-lock equipped with mechanical and electrical protection devices, lifting interruption control, OPS system, travel speed limiting and other functions ensure safe operations.
- / The LED lighting system ensures the brightness of the lighting within the operating range.
- / A visual reversing radar is provided for the standard configuration and other options such as an automatic fire extinguishing system, tire pressure monitoring, overload protection, etc. can be provided.



## Fully-suspended all-round vision cab

- / The movable fully-suspend cab, easy for maintenance.
- / With the vehicle frame damper connected and the tight sound and heat insulation design, most vibration and noise are shielded.
- / The largely-curved front and rear windows, all-glass left and right doors and large glass ceiling enable a broad view.
- / An inclinable telescopic steering column and fully-suspended adjustable seat with a high backrest and safety belt, with seat sensing and driving position sensing functions.
- / A high-power cooling and heating air conditioner, two ventilation modes - internal and external circulation, sunshades, speed-adjustable wipers and defrosting function make driving more comfortable.





## TECHNICAL SPECIFICATIONS

|  |  |
|--|--|
| Type of lifting system                                   | Two vertical twistlocks  |
| Type of stacking   | Normal and block stacking  |
| Spreader weight (TW)                                     | 3600 kgs   |
| Carriage weight (MPS)                                    | 1050 kgs   |
| Lifting capacity (SWL)                                   | 9 tonnes   |
| Telescopic positions                                     | 20 and 40ft  |
| Telescoping speed, 20-40ft                               | < 12 sec.*   |
| Telescoping speed, 40-20ft                               | < 14 sec.*   |
| Sideshift  | ± 600  |
| Mechanical pile slope (MPS), vertical floating end-posts | At 20ft position: approx. 200 mm<br>At 40ft position: approx. 200 mm |
| Hydraulics, operating pressure up to                     | 140 bar  |
| Hydraulics, flow   | 40-60 L/min  |
| Electric - control voltage                               | 24 VDC   |
| Communication  | CAN 2.0B   |
| Colour   | Black grey RAL 7021  |

\* Calculated speed at 60 L/min

## Single handling container spreader Vertical Twistlocks.

### Suitable for:

- / 20' or 40' ISO containers of 8' (2.44 m) width.
- / Approx. 2.45-2.50 m wide "pallet-wide" 20' or 40' containers, with ISO-like 'chamfered' corner castings.
- / With speed limitation for laden/unladen.

### Not suitable for:



- / Approx. 2.45 - 2.60 m wide "CPC" containers (Cellular Pallet-wide Containers) with non-ISO corner castings.



Improved design with built-in cabling and larger bending radius for hydraulic hose between pocket and end-post.



INNOVATION head.



## Features

| Transmission   | Standard | Options |
|--|----------|---------|
| Pneumatic tyre   | ●        |         |
| Solid smooth tire  |          | ○       |
| Steering system  |          |         |
| Fully hydraulic power steering                                 | ●        |         |
| Centralized lubrication system (machine)                       | ●        |         |
| Automatic Lubrication System                                   |          | ○       |
| Power system   |          |         |
| Extended exhaust pipe  | ●        |         |
| Lockable fuel cap  | ●        |         |
| Spark arrester   |          | ○       |
| Pre-cleaner air filter   | ●        |         |
| Truck  |          |         |
| Tow pin  | ●        |         |
| Electrostatic discharge chain                                  |          | ○       |
| Rear-view mirror on right & left mudguards                     | ●        |         |
| Operating system   |          |         |
| Integrated joystick  | ●        |         |
| Adjustable steering column                                     | ●        |         |
| Adjustable armrest   | ●        |         |
| Hydraulic system   |          |         |
| Operation proportion control                                   | ●        |         |
| Cab  |          |         |
| Cabin  | ●        |         |
| Climate control system (air-conditioning and heater)           | ●        |         |
| Radio  | ●        |         |
| Sunshade   | ●        |         |
| USB charging interface   | ●        |         |
| Clothes hanger hook  | ●        |         |
| Reading light  | ●        |         |
| 1 x 24V power supply   |          | ○       |
| 1 x 12V power supply   |          | ○       |
| License plate frame  |          | ○       |
| Fan  | ●        |         |
| Lifting components   |          |         |
| Duplex mast  | ●        |         |
| Standard lifting height  | ●        |         |
| Optional lifting height  |          | ○       |
| Spreader & twistlock double protection                         | ●        |         |
| Emergency descent  | ●        |         |
| Twistlock counter  | ●        |         |
| 2 x Spreader twistlock light                                   | ●        |         |
| Other  |          |         |
| Standard color   | ●        |         |
| User defined colour  |          | ○       |
| Fire extinguisher (2kg/4kg)                                    |          | ○       |
| Vehicle toolkit  | ●        |         |
| Mast automatic vertical realignment                            |          | ○       |
| Lifting height indicator on display                            |          | ○       |
| Dynamic speed Limit depending of lift height(customer defined) |          | ○       |
| Heating pack for the cold region                               |          | ○       |
| FIMS(Fleet intelligent management system)                      | ●        |         |

| Electrical System   | Standard | Options |
|---|----------|---------|
| Operator Presense System (OPS) with buzzer                | ●        |         |
| LCD display screen  | ●        |         |
| Main power switch   | ●        |         |
| Emergency power off switch                                | ●        |         |
| Maintenance-free 24V lead acid battery                    | ●        |         |
| Reverse buzzer  | ●        |         |
| High decible horn   | ●        |         |
| LED lights (entire vehicle)                               | ●        |         |
| 2 x Working light on front mudguard                       | ●        |         |
| 2 x Front working light on top of cabin                   | ●        |         |
| 2 x Rear working light on top of cabin                    | ●        |         |
| 2 x Working light on both sides of mast                   | ●        |         |
| Reverse sensor  | ●        |         |
| Rearview camera system                                    | ●        |         |
| Rearview camera system with memory                        |          | ○       |
| Front & rearview camera system                            |          | ○       |
| Front & rearview camera system with memory                |          | ○       |
| 4 directions camera system with single display            |          | ○       |
| 4 directions camera recording system with single display  |          | ○       |
| In cabin CCTV   |          | ○       |
| Rear blue safety light                                    |          | ○       |
| Front and rear blue safety light                          |          | ○       |
| Three sided blue danger zone light                        |          | ○       |
| Overspeed alarm   |          | ○       |
| Speed limitation  |          | ○       |
| Voice reverse alarm                                       |          | ○       |
| Automatic fire suppression system                         |          | ○       |
| Two-way radio   |          | ○       |
| Weight indicator in display                               |          | ○       |
| Flashing warning light (non rotating) with control switch | ●        |         |
| Tyre pressure monitoring                                  |          | ○       |
| On-board diagnostics system                               | ●        |         |
| Override switch   | ●        |         |
| Engine fault alarm  | ●        |         |
| Engine oil pressure alarm indicator                       | ●        |         |
| Air filter warning indicator                              | ●        |         |
| Water temperature indicator                               | ●        |         |
| Hour meter  | ●        |         |
| Battery charge indicator                                  | ●        |         |
| Low hydraulic pressure alarm indicator                    | ●        |         |
| Hydraulic oil filter warning indicator                    | ●        |         |
| Oil gauge   | ●        |         |
| Fuel-water separator warning indicator                    | ●        |         |
| Oil temperature gauge                                     | ●        |         |
| Pre-heat indicator  | ●        |         |
| Drive mode indicator                                      | ●        |         |
| Parking brake indicator                                   | ●        |         |
| Service indicator   | ●        |         |