

HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.









Forklift" App

Facebook

Follow us on YouTube





to the European Safety Requirements

XH SERIES HIGH-VOLTAGE TELEHANDLER

with capacity of 2,500 to 3,500kg

2025 VERSION 7/COPYRIGHT 2025/05

Making Material Handling Easier

XH SERIES HIGH-VOLTAGE TELEHANDLER

25-60

HANGCHA Family-Design exterior, ergonomic cab, intuitive HMI system and premium driving comfort experience.

ANGCHA

HIGH-PERFORMANCE MACHINES IN ANY SITUATION



THREE STEERING MODES:



TWO DRIVING MODES: TWO-WHEEL DRIVE

The first compact telehandler with 310V high-voltage lithium battery in industry, high voltage DC fast-charging technology. Make a charge from 30% to 80% only in 30 minutes.





With permanent magnet synchronous motor (PMSM) technology, can reach top speed: 25 km/h, maximum grade ability: 45%, and industry-leading performance in its class.









The machine is equipped with quick change device, which can realize the quick replacement of different attachments. This enables various operations including fork loading, shovel loading, clamping, aerial work, etc.



COMFORT

Driver assistance system and easy control

- 1 The cab can be equipped with air conditioning, radio, and USB charging port as option.
- 2 Adjustable suspension seat can provide more ergonomic.
- I Full-proportional joystick, smooth and coordinated movements, smooth and steady on start and stop, boom luffing and telescoping support multi-movements.
- 4 7 inch display, real-time machine status monitoring, integrated intelligent fault diagnosis system.







SAFETY

- Lithium iron phosphate battery pack---high safety & proven reliability.

- and overloading, and timely restrict actions to avoid accidents.

MAINTENANCE

The machine is equipped with a maintenance arm to prevent the risk of accidental fall of the arm frame during maintenance. ■ Wide-angle tilting cover ensures easy maintenance access

Eller

25-60



The lighting system is excellent. Besides the High and low beam headlights, LED high-brightness working lights are also provided in the cab front and rear and the boom respectively, ensuring operation in night scenarios. Equipped with overload monitoring system, it can conduct real-time dynamic monitoring to prevent overturning



Features

Truck	Standard	Options
Air conditioner		0
Reverse radar		0
Rotating Amber beacon		0
Fire extinguisher in cabin or at rear		0
Rear Camera + Monitor		0
Quick exchange fork carriage		0
	•	
Load backrest	•	
Adjustable suspension seat	•	
Flame retardant leather seats	•	
Traction device	•	
Load moment limiter Overload monitoring devise	•	
Left operable window	•	
Horn	•	
Key switch	•	
Wide angle L/R rearview mirrors	•	
Panoramic reversing mirror		
Front wiper with water spray function	•	
Rear window wiper	•	
High and low beam headlights	•	
Front and rear work lights		
Working light		
Reverse light		
Windshield protective frame		0
Fire Extinguisher		0
Foam filled tire		0
Quick change heavy Duty Multi-Purpose Bucket		0
Quick change neavy bitly Molti-Polipose bocket Quick change soft bale clamp		0
Quick change solt bale claimp Quick change crane arm		
Forklift arm		0
		0
Steering		
Three steering modes		
Adjustable steering column	•	
Hydraulic		
Hydraulic quick coupler	•	
Tilt cylinder self-locking valve	•	
Self locking valve for telescopic oil cylinder	•	
Lifting cylinder self-locking valve	•	
Lifting cylinder maintenance arm		
Hydraulic Oil Filter	•	
Hydraulic oil air filter	•	
Hydraulic oil dipstick	•	
Power		
2WD and 4WD switch function	•	
Three gears		
Transmission		
Wet brake Limited slip differential	•	
•		
Hydraulic power steering		
Control		
Dual axis proportional control handle		
Emergency stop switch		
Parking brake		
Safety		
Warning light	•	
Reverse alarm	•	
		0
Reverse camera		0
		\cup
Reverse radar		
Reverse radar		
Reverse radar Accept various attachments		0
Reverse camera Reverse radar Accept various attachments Fork-Mounted Extendable Truss Fork-Mounted working platform		
Reverse radar Accept various attachments		0 0 0

Electronics	Standard	Options
Build-in charger	•	
DC fast charging port	•	
ault self diagnosis function	•	
7-inch color multifunctional display screen	•	
Aotor temperature display	•	
Varning lamp for not fastening the seat belt	•	
Vater cooling system	•	
eater	•	
Reading light	•	
adio	•	
ISB charge port		

