



ZHEJIANG HANGCHA IMP. & EXP. CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com
www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



Download "Hangcha
Forklift" App



ISO45001
ISO45001:2018



ISO14001
ISO14001:2015



ISO9001
ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

2023 VERSION 3 / COPYRIGHT 2023 / 11

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

XH SERIES HIGH-VOLTAGE LITHIUM BATTERY REACHSTACKER

with capacity of 45,000kg

LI-ION
TECHNOLOGY

INNOVATIVE LITHIUM-ION

REACH
THE SKY



HANGCHA

The World of Hangcha

XH SERIES HIGH-VOLTAGE LITHIUM BATTERY REACHSTACKER

The RS4531CH-XHJG electric reach stacker is a newly developed product based on Hangcha's new lithium battery platform of XH series and years of experience in R&D of internal combustion reach stacker. With the new technologies of three-phase drive motor, separate pump control, kinetic energy recovery, etc., the electric reach stacker can make quick operation response at low operation energy consumption. With intelligent and efficient performance, the vehicle is energy-saving, safe and reliable.

VOLTAGE

618 V

CHARGING TIME (20-100%)

1.5Hour

VEHICLE WATER RESISTANCE

IPX4

SPEED MODELS

3 S/P/E mode
(Super/Power/Eco)

PROTECTION RATE

IP67

Exterior

/ With the inherited exterior design of internal combustion reach stackers—pitch-down streamlined design and a smooth, vivid and sturdy profile, the vehicle has smooth coloring, a simple and elegant logo, as well as largely-curved front and rear windows, a large glass ceiling and all-glass side doors to enable a broad view.

THE *Plus*
FOR YOUR
BUSINESS





FASTER & MORE EFFICIENCY.

Fast charging makes it possible for the whole vehicle to work continuously, shortening the waiting time and greatly improving efficiency.

Through disruptive battery and fast charging technology, the charging time is greatly shortened.

4000
CYCLES OF CHARGING



Under normal charging and discharging conditions, the lithium battery of Hangcha products has a capacity retention rate of more than 75% and a life span of up to 10 years after 4000 cycles of charging and discharging.

HIGH-VOLTAGE

423kWh

Battery capacity



Maintainability

/ An easy-to-remove hood; all the maintenance points are in easily accessible positions to facilitate repair and maintenance of electrical elements.



Intelligence

- / High-definition LCD instruments have simple graphical interfaces to display data clearly. The interfaces can be switched to be shown in Chinese and English.
- / A vehicle central control system, which has bus architecture, and interconnected motor, battery and heat management control system.
- / Fault diagnosis and alarm functions facilitate maintenance.
- / Display: boom length, actual load, maximum load, boom height, jaw angle, outreach, load percentage bar, alarm code, etc.



Advancement

- / A high-torque permanent magnet synchronous motor provides strong power for the vehicle with performance indicators benchmarked against that of internal combustion forklifts.
- / A 618V high-voltage platform with low system loss and a standard chilled water tank for heavy-duty truck to achieve good heat dissipation.
- / The vehicle has independently developed VCU program along with PDU+MCU+BMS+DC/DC to form a reliable and efficient drive system with flexible function configuration.
- / With motor, electric control and battery adopting liquid-cooling heat dissipation to achieve better heat dissipation, the forklift can absolutely carry out long-time and high-intensity operations.

	Type	Unit	Permanent Magnet Synchronous Motor
Drive motor	Output Power (Peak)	kW	380
	Output Torque (Peak)	N·m	4600

Intelligent Control System

Bus meter control module	Motor control module	Spreader Control Module	Hydraulic Control Module
Lithium battery control module	Thermal Management Control Module	Remote management system	

Functions such as single-joystick operation, spreader's vertical lifting, combined operations, throttle following, etc. make operations more efficient.



Safety

- / The cover of the vehicle is designed to be sealed so that the protection level of the vehicle reaches level IPX4.
- / The electrical system has high-voltage interlocking, insulation protection and monitoring, and potential balancing functions to offer vehicle-grade safety.
- / Both the battery and junction box have MSD(Manual Service Disconnect) maintenance switches to enable one-click power-down and safer maintenance.
- / Key structural parts in reference to internal combustion forklifts have been verified highly reliable by the market for many years.
- / The 6-probe visual reversing radar and wide-view cab offer a wide view without a blind corner.
- / Safety technologies such as seat sensing, dynamic antitipping protection, longitudinal dual anti-tipping protection, spreader twist-lock dual protection, startup anti-stalling protection, fault protection, etc. are used to ensure safe operations at all times.



All the motor, electronic controls and high-voltage components reach the dust and water resistance level of IP67, a high protection level adequate to withstand harsh operating environments and ensure safety and reliability.



The high-voltage lithium battery is equipped with an automatic fire extinguisher for the standard configuration. The vehicle is equipped with a pipe network automatic fire extinguisher for the standard configuration.

Ultra-long battery life

- / Standard large-capacity lithium battery meets long battery life requirements.
- / Both the drive and operating systems are efficient vehicle-grade permanent magnet synchronization systems with low energy consumption.
- / 618V high-voltage platform, less vehicle current and minimal system heat loss
- / Braking energy and potential energy recovery effectively prolongs operating time.
- / A double-gun quick charging port offers a full charge in no more than 2 hours.



ELME new-generation container spreader



- / For the new-generation ELME817 series telescopic container spreader, the design of the telescopic beam, turntable, etc. are optimized, so that the structural strength is increased, the weight of the spreader is 16% less than that of the spreader of the last generation and the service life is prolonged by 30%.
- / The arrangement of the oil cylinder is changed to be more conducive to maintenance.
- / Design of the hydraulic system is optimized, so that the spreader system has less pressure loss and is more energy-saving and efficient.
- / With electro-hydraulic proportional control, the speed is adjustable and the rotation angle of the spreader can be smoothly and finely controlled.
- / The latest Neuron programmable controller is used so that more optional features can be developed. Fault code information is provided according to the J1939 protocol so that fault query is quick and simple.
- / The twist-lock interlock device (mechanical and electro-hydraulic) and the real-time indication of the action indicator are provided to avoid:
 - the container is lifted when less than 4 corners are locked;
 - the twist-lock is opened when the container is lifted.
- / The lift interrupter can prevent the container from being lifted when the twist-lock is partly twisted. The lift operations can be performed only when the twist-lock is locked or unlocked.

Efficient hydraulic system

- / American PARKER's combined hydraulic valves, PARKER's variable hydraulic pump and the load sensing hydraulic system.
- / Flexible and precise electric proportional control.
- / Light load high-speed lifting increases work efficiency. Independent temperature control and the large-size hydraulic oil cooler meet the work in the environment of up to 50 degrees.
- / Perfect high and low pressure oil filters improve the reliability of the hydraulic system.
- / Multiple hydraulic test points are set to simplify repair and maintenance work.



Fully-suspended all-round vision cab

- / The suspended cabin, easy for maintenance.
- / With the vehicle frame damper connected and the tight sound and heat insulation design, most vibration and noise are shielded.
- / The largely-curved front and rear windows, all-glass left and right doors and large glass ceiling enable a broad view.
- / An inclinable telescopic steering column and fully-suspended adjustable seat with a high backrest and safety belt, with seat sensing and driving position sensing functions
- / A high-power cooling and heating air conditioner, two ventilation modes - internal and external circulation, sunshades, speed-adjustable wipers and defrosting function make driving more comfortable.



Appearance and performance

- / The pitch-down streamlined design of the vehicle presents a vivid and sturdy profile.
- / The optimized counterweight contour greatly reduces the turning radius of the vehicle, broadens the side rear and front rear views, and makes driving simple and safe.
- / The left and right stair handrails, mudguard handrails, together with the anti-skid pedals and anti-skid paper, fully protect the safety of personnel.



Stylish and comfortable

- / **Fashionable and high-end modeling elements**
The pitch-down streamlined design presents a vivid and sturdy profile. Smooth coloring and the simple and elegant logo highlight fashionable and high-end design elements.
- / **Ergonomic control platform**
The ergonomically-designed control platform equipped with reasonably-arranged comfortable-feel buttons enables comfortable and accurate operations, plus the adjustable steering wheel and the suspended seat with an adjustable backrest, making the operator more comfortable.
- / **Quiet, fully-suspended all-round vision cab**
In the cab, noises are less than 78dB and there are a cooling and heating air conditioner, sunshades, a reading light, a radio and other equipment to provide a comfortable operating environment.



Standard Specification

- | | | |
|--|--|--|
| / Standard lifting height | / Maintenance-free 24V lead acid battery | / Dual charging ports |
| / Spreader & twistlock double protection | / Reverse buzzer | / Override switch |
| / Emergency descent | / High decible horn | / Central control panel for lighting system |
| / Twistlock counter | / LED lights (entire vehicle) | / Hour meter |
| / Spreader swing prevention | / 4 x Working light on front mudguard | / Battery charge indicator |
| / 2 x Spreader twistlock light | / 4 x Working light on boom | / Low hydraulic pressure alarm indicator |
| / Standard color | / 2 x Rear working light | / Hydraulic oil filter warning indicator |
| / Vehicle toolkit | / Reverse sensor | / Drive mode indicator |
| / Pneumatic tyre | / Rearview camera system | / Parking brake indicator |
| / Fully hydraulic power steering | / Weight indicator in display | / Service indicator |
| / Tow pin | / Flashing warning light (non rotating) with control switch | / Automatic throttle control (lift / tilt / spreader) |
| / Rear-view mirror on right & left mudguards | / On-board diagnostics system | / Cabin |
| / Separate brake oil tank | / Water cooling system for lithium battery | / Climate control system (air-conditioning and heater) |
| / Integrated joystick | / Automatic fire suppression system | / Radio |
| / Adjustable steering column | / Automatic fire suppression system for lithium battery pack | / Sunshade |
| / Adjustable armrest | / Manual Service Disconnect (MSD) switch | / USB charging interface |
| / Variable hydraulic pump system | / High voltage interlock | / Clothes hanger hook |
| / Operation proportion control | / Insulation protection | / Reading light |
| / Higher lifting speed at light load | / Power-on self-test | / Fan |
| / Operator Presense System (OPS) with buzzer | / Energy recovery (braking regeneration) | / Movable Cabin |
| / LCD display screen | / Energy recovery (descent regeneration) | / Overload protection |
| / Main power switch | / Vehicle Control Unit (VCU) | / Lifting height indicator on display |
| / Emergency power off switch | | |

Options

- | | | |
|--|--|---|
| / 4 x Spreader twistlock camera | / 4 directions camera system with single display | / Voice reverse alarm |
| / User defined colour | / 4 directions camera recording system with single display | / Two-way radio |
| / Fire extinguisher (2kg/4kg) | / In cabin CCTV | / Eccentric load weighing (with printer) |
| / Heating pack for the cold region | / Rear blue safety light | / Tyre pressure monitoring |
| / Solid tyre | / Front and rear blue safety light | / Vertical lift control |
| / Centralized lubrication system (machine) | / Three sided blue danger zone light | / Turning deceleration |
| / Electrostatic discharge chain | / Overspeed alarm | / 1 x 24V power supply |
| / Rearview camera system with memory | / Speed limitation | / 1 x 12V power supply |
| / Front & rearview camera system | | / License plate frame |
| / Front & rearview camera system with memory | | / Dynamic speed Limit depending of lift height(customer defined) |